



Product Service

Attestation of Conformity

No. E8A 086470 0086 Rev. 03

Holder of Certificate: **Ginlong Technologies Co., Ltd.**
No.57 Jintong Road
Binhai Industrial Park, Xiangshan
315712 Ningbo, Zhejiang
PEOPLE'S REPUBLIC OF CHINA

Name of Object: **Converter**
(PV Grid-Tied Inverter)

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with all essential requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 64772218005804

Date, 2022-04-22

(Tony Liu)

Page 1 of 6

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. E8A 086470 0086 Rev. 03

Model(s):

Solis-1P2.5K-4G, Solis-1P3K-4G, Solis-1P3.6K-4G, Solis-1P4K-4G, Solis-1P4.6K-4G, Solis-1P5K-4G-MX, Solis-1P5K-4G, Solis-1P6K-4G, Solis-1P2.5K-4G-C, Solis-1P3K-4G-C, Solis-1P3.6K-4G-C, Solis-1P4K-4G-C, Solis-1P4.6K-4G-C, Solis-1P5K-4G-MX-C, Solis-1P5K-4G-C, Solis-1P6K-4G-C, S5-GR1P2.5K, S5-GR1P3K, S5-GR1P3.6K, S5-GR1P4K, S5-GR1P4.6K, S5-GR1P5K, S5-GR1P6K, S6-GR1P2.5K, S6-GR1P3K, S6-GR1P3.6K, S6-GR1P4K, S6-GR1P4.6K, S6-GR1P5K, S6-GR1P6K, S6-GR1P2.5K-R, S6-GR1P3K-R, S6-GR1P3.6K-R, S6-GR1P4K-R, S6-GR1P4.6K-R, S6-GR1P5K-R, S6-GR1P6K-R, S6-GR1P3K-LV, S6-GR1P2.5K-LV

Trade name:

solis



Description of Object:

Models	Solis-1P2.5K-4G Solis-1P2.5K-4G-C	Solis-1P3K-4G Solis-1P3K-4G-C	Solis-1P3.6K-4G Solis-1P3.6K-4G-C	Solis-1P4K-4G Solis-1P4K-4G-C
PV input ratings:				
Max. input voltage:	550Vd.c.	600Vd.c.	600Vd.c.	600Vd.c.
MPP voltage range:	50-450Vd.c.	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 11Ad.c.	2 x 11Ad.c.	2 x 11Ad.c.	2 x 11Ad.c.
Isc PV (absolute maximum):	2 x 17.2Ad.c.	2 x 17.2Ad.c.	2 x 17.2Ad.c.	2 x 17.2Ad.c.
AC output ratings:				
Rated grid voltage:	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.
Rated grid frequency:	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Rated output power:	2500W	3000W	3600W	4000W
Max. AC output active power:	2800W	3300W	4000W	4400W
Max. AC output apparent power:	2800VA	3300VA	4000VA	4400VA
Max. continuous output current:	13.3Aa.c.	15.7Aa.c.	16Aa.c.	21Aa.c.



Product Service

Attestation of Conformity

No. E8A 086470 0086 Rev. 03

Models	Solis-1P4.6K-4G Solis-1P4.6K-4G-C	Solis-1P5K-4G Solis-1P5K-4G-C	Solis-1P5K-4G-MX Solis-1P5K-4G-MX-C	Solis-1P6K-4G Solis-1P6K-4G-C
PV input ratings:				
Max. input voltage:	600Vd.c.	600Vd.c.	600Vd.c.	600Vd.c.
MPP voltage range:	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 11Ad.c.	2 x 11Ad.c.	2 x 11Ad.c.	2 x 11Ad.c.
Isc PV (absolute maximum):	2 x 17.2Ad.c.	2 x 17.2Ad.c.	2 x 17.2Ad.c.	2 x 17.2Ad.c.
AC output ratings:				
Rated grid voltage:	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.
Rated grid frequency:	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Rated output power:	4600W	5000W	4999W	6000W
Max. AC output active power:	5000W	5000W	4999W	6000W
Max. AC output apparent power:	5000VA	5000VA	4999VA	6000VA
Max. continuous output current:	23.8Aa.c.	25Aa.c.	21.7Aa.c.	27.3Aa.c.



Product Service

Attestation of Conformity

No. E8A 086470 0086 Rev. 03

Models	S5-GR1P2.5K S6-GR1P2.5K S6-GR1P2.5K-R	S5-GR1P3K S6-GR1P3K S6-GR1P3K-R	S5-GR1P3.6K S6-GR1P3.6K S6-GR1P3.6K-R	S5-GR1P4K S6-GR1P4K S6-GR1P4K-R
PV input ratings:				
Max. input voltage:	550Vd.c.	600Vd.c.	600Vd.c.	600Vd.c.
MPP voltage range:	50-450Vd.c.	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 14Ad.c.	2 x 14Ad.c.	2 x 14Ad.c.	2 x 14Ad.c.
Isc PV (absolute maximum):	2 x 22Ad.c.	2 x 22Ad.c.	2 x 22Ad.c.	2 x 22Ad.c.
AC output ratings:				
Rated grid voltage:	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.
Rated grid frequency:	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Rated output power:	2500W	3000W	3600W	4000W
Max. AC output active power:	2800W	3300W	4000W	4400W
Max. AC output apparent power:	2800VA	3300VA	4000VA	4400VA
Max. continuous output current:	13.3Aa.c.	15.7Aa.c.	16Aa.c.	21Aa.c.

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. E8A 086470 0086 Rev. 03

Models	S5-GR1P4.6K S6-GR1P4.6K S6-GR1P4.6K-R	S5-GR1P5K S6-GR1P5K S6-GR1P5K-R	S5-GR1P6K S6-GR1P6K S6-GR1P6K-R
Max. input voltage:	600Vd.c.	600Vd.c.	600Vd.c.
MPP voltage range:	90-520Vd.c.	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 14Ad.c.	2 x 14Ad.c.	2 x 14Ad.c.
Isc PV (absolute maximum):	2 x 22Ad.c.	2 x 22Ad.c.	2 x 22Ad.c.
Rated grid voltage:	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.	1/N/PE 220/230Va.c.
Rated grid frequency:	50/60Hz	50/60Hz	50/60Hz
Rated output power:	4600W	5000W	6000W
Max. AC output active power:	5000W	5000W	6000W
Max. AC output apparent power:	5000VA	5000VA	6000VA
Max. continuous output current:	23.8Aa.c.	25Aa.c.	27.3Aa.c.

Models	S6-GR1P3K-LV	S6-GR1P2.5K-LV
Max. input voltage:	600Vd.c.	600Vd.c.
MPP voltage range:	90-520Vd.c.	90-520Vd.c.
Max. input current:	2 x 14Ad.c.	2 x 14Ad.c.
Isc PV (absolute maximum):	2 x 22Ad.c.	2 x 22Ad.c.
Rated grid voltage:	1/N/PE 110Va.c.	1/N/PE 110Va.c.
Rated grid frequency:	60Hz	60Hz
Max. AC output active power:	3000W	2500W
Max. AC output apparent power:	3000VA	2500VA
Max. continuous output current:	27.3Aa.c.	22.7Aa.c.

General specifications:		
Models	S6 series moldes	all other models
Adjustable cos(φ)	-0.8...1...+0.8	
Protection class	I	
Degree of protection	IP66	IP65
Overvoltage category	II(PV), III(MAINS)	
Ambient temperature	-25°C ... +60°C	
Inverter topology	Non-isolated	

Page 5 of 6

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. E8A 086470 0086 Rev. 03

**Tested
according to:**

EN IEC 61000-6-1:2019
EN IEC 61000-6-2:2019
EN IEC 61000-6-3:2021
EN IEC 61000-6-4:2019
EN 55011:2016/A11:2020
EN 55011:2016/A2:2021

Page 6 of 6

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.