




Product Service

CERTIFICATE

No. Z2 099333 0080 Rev. 02

Holder of Certificate: **LONGi Green Energy Technology Co., Ltd.**
No. 388, Middle Hangtian Road
Chang'an District
710100 Xi'an City, Shaanxi
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704062000945-02

Valid until: 2027-05-04

Date, 2022-05-09

(Zhulin Zhang)



CERTIFICATE

No. Z2 099333 0080 Rev. 02

Model(s):

LR6-72-xxxM, (xxx=320 to 350 in step of 5)
LR6-60-xxxM, (xxx=270 to 300 in step of 5)
LR6-72PE-xxxM, (xxx=340 to 380 in step of 5)
LR6-60PE-xxxM, (xxx=280 to 320 in step of 5)
LR6-72MP-xxxM, (xxx=340 to 380 in step of 5)
LR6-60MP-xxxM, (xxx=280 to 320 in step of 5)
LR6-72BK-xxxM, (xxx=320 to 350 in step of 5)
LR6-60BK-xxxM, (xxx=270 to 300 in step of 5)
LR6-72PB-xxxM, (xxx=340 to 380 in step of 5)
LR6-60PB-xxxM, (xxx=280 to 320 in step of 5)
LR6-72HPB-xxxM, (xxx=360 to 385 in step of 5)
LR6-60HPB-xxxM, (xxx=300 to 320 in step of 5)
LR4-72HPB-xxxM, (xxx=405 to 445 in step of 5)
LR4-60HPB-xxxM, (xxx=335 to 380 in step of 5)
LR6-60HIB-xxxM, (xxx=300 to 320 in step of 5)
LR4-60HIB-xxxM, (xxx=335 to 370 in step of 5)
LR4-60ZPB-xxxM, (xxx=345 to 365 in step of 5)
LR4-60ZIB-xxxM, (xxx=345 to 365 in step of 5)
LR4-60HP-xxxM, (xxx=350 to 375 in step of 5)
LR4-66HP-xxxM, (xxx=395 to 415 in step of 5)
LR5-54HPB-xxxM, (xxx=390 to 410 in step of 5)
LR5-54HIB-xxxM, (xxx=390 to 410 in step of 5)
xxx is standing for rated output power at STC

Parameters:

Construction:	Framed, with Junction box, cable and connector.
Safety Class:	Class II
Max. System Voltage:	1000V DC
Fire Safety Class:	Class C according to UL790.
Test method of Salt mist test:	Test method 1 & 6

Tested according to:

IEC 61215-1:2016
IEC 61215-1-1:2016
IEC 61215-2:2016
IEC 61730-1:2016
IEC 61730-2:2016
IEC 61701:2020